



**0580 Desert Dune**



**Zenith Plus Collection**

## Product Specifications

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>Color Number</b>       | 0180-0880                                       |
| <b>Dimension</b>          | 7.17" Width x 60.63" Length                     |
| <b>Construction</b>       | Stone Polymer Composite                         |
| <b>Locking System</b>     | Välinge 5G                                      |
| <b>Thickness</b>          | 8mm (6.5mm SPC + 1.5mm PAD)                     |
| <b>Wear Layer</b>         | 20mil (0.5mm)                                   |
| <b>Underlayment type</b>  | HD [3X] Waffle EVA                              |
| <b>Surface</b>            | EIR                                             |
| <b>Edge Profile</b>       | Painted Bevel                                   |
| <b>Installation</b>       | Floating                                        |
| <b>Installation Grade</b> | Install on All Levels                           |
| <b>Warranty</b>           | Lifetime Residential / 15 Year Light Commercial |
| <b>Area per Carton</b>    | 18.10 SF                                        |
| <b>Area per Pallet</b>    | 905 SF                                          |
| <b>PC per Carton</b>      | 6 Planks                                        |
| <b>Acoustic Rating</b>    | STC 77 / IIC 76                                 |

# Technical Test Data

|                         |                   |                                       |
|-------------------------|-------------------|---------------------------------------|
| Dimensional Stability   | ASTM F2199-09     | Pass: $\leq 0.01$ in. per Linear Foot |
| Resistance to Chemicals | ASTM F925-1       | Rating 0: No Change                   |
| Formaldehyde Emissions  | ASTM D5116-10     | No Formaldehyde                       |
| Slip Resistance         | DIN51130          | R10                                   |
| Abrasion                | ASTM D4060        | 0.002% Mass Loss                      |
| Curling                 | ISO 23999 / EN434 | 0.03mm                                |
| Reaction to Fire        | EN13501-1         | Class BFL-S1                          |
| Static Load             | ASTM F970         | 0.00mm                                |
| Antibacterial Activity  | ASTM G21-15       | Pass: No Growth Observed              |
| Critical Radiant Flux   | ASTM E648-17      | Flux: $\geq 0.45$ W/cm <sup>2</sup>   |



FloorScore Certified to meet (IAQ) standards, it qualifies for many green building schemes including LEED v4, WELL, BREEAM, CHPS, and Green Globes.

The product is made from 100% virgin materials, no recycled materials are used in manufacturing, which ensures product stability and durability.

ColorMatching moldings available for T-molding, Reducer, and Stair Nosing.

Featuring a commercial-grade 20mil wear layer, painted bevels add to a more realistic appearance.





**0180 Golden Harvest**



**0280 Autumn Oak**



**0380 Almond Cream**



**0480 Urban Steel**



**0580 Desert Dune**



**0780 Sunset Gold**



**0880 Savannah Ridge**