



0565 Prairie Wheat



Zenith Collection

Product Specifications

Color Number	0165-0665
Dimension	7.17" Width x 60.63" Length
Construction	Stone Polymer Composite
Locking System	Välinge 5Gi
Thickness	6.5mm (5mm SPC + 1.5mm PAD)
Wear Layer	20mil (0.5mm)
Underlayment type	HD [3X] Waffle EVA
Surface	Oak Emboss (Random EIR)
Edge Profile	Painted Bevel
Installation	Floating
Installation Grade	Install on All Levels
Warranty	30 Year Residential / 10 Year Light Commercial
Area per Carton	24.15 SF
Area per Pallet	1,207.5 SF
PC per Carton	8 Planks
Acoustic Rating	STC 75 / IIC 74

Technical Test Data

Dimensional Stability	ASTM F2199-09	Pass: ≤ 0.01 in. per Linear Foot
Resistance to Chemicals	ASTM F925-1	Rating 0: No Change
Formaldehyde Emissions	ASTM D5116-10	No Formaldehyde
Slip Resistance	DIN51130	R10
Abrasion	ASTM D4060	0.002% Mass Loss
Curling	ISO 23999 / EN434	0.03mm
Reaction to Fire	EN13501-1	Class BFL-S1
Static Load	ASTM F970	0.00mm
Antibacterial Activity	ASTM G21-15	Pass: No Growth Observed
Critical Radiant Flux	ASTM E648-17	Flux: ≥ 0.45 W/cm ²



FloorScore Certified to meet (IAQ) standards, it qualifies for many green building schemes including LEED v4, WELL, BREEAM, CHPS, and Green Globes.

The product is made from 100% virgin materials, no recycled materials are used in manufacturing, which ensures product stability and durability.

ColorMatching moldings available for T-molding, Reducer, and Stair Nosing.

Featuring a commercial-grade 20mil wear layer, painted bevels add to a more realistic appearance.





0165 Caramel Swirl



0265 Sandstone



0365 Driftwood



0465 Terracotta



0565 Prairie Wheat



0665 Misty Morning